



## VP® ULTRA POWER Ashless Gas Engine Oil

### DESCRIPTION

**ULTRA POWER™ Ashless Gas Engine Oil** is a premium ashless detergent and dispersant engine oil. It is specifically formulated for the unique requirements of 2-stroke and certain 4-stroke cycle stationary natural gas engines where an ashless engine oil is preferred.

ULTRA POWER Ashless Gas Engine Oil, available in SAE grades 30, 40, and 15W-40, meets and exceeds stringent OEM performance standards for stationary engines.

### PERFORMANCE BENEFITS

- Superior wear protection for critical engine components
- Maximum resistance to sludge ash, and varnish deposit formation
- Minimizes pre-ignition and detonation
- Promotes optimum engine cleanliness
- Maximum corrosion protection for sensitive bearings, including copper-lead
- Reduced maintenance and associated equipment downtime
- Outstanding low-temperature performance for cold-starts (SAE 15W-40)

### PRODUCT APPLICATION

ULTRA POWER Ashless Gas Engine Oil is recommended for the following engine oil recommendations:

Ajax, Arrow, Clark-Dresser  
Cooper Bessemer and Worthington (2-stroke)  
Waukesha VR and Intermediate/Clinton series (4-stroke)  
Caterpillar G300 NA  
Fairbanks-Morse/MEP (2-stroke)

Typical Physical Properties				
Property	Method			
<b>SAE Grade</b>		<b>30</b>	<b>40</b>	<b>15W-40</b>
Viscosity, cSt @40°C	D-445	100.0	120.0	104.0
Viscosity, cSt @100°C	D-445	11.5	13.0	13.9
Viscosity Index	D-2270	100	100	140
API Gravity, @60°F	D-1250	30.1	29.1	30.2
Flash Point, COC, °C(°F)	D-92	260 (500)	260 (500)	228 (443)
Pour Point, °C(°F)	D-97	-23 (-11)	-23 (-11)	-30 (-22)
Phosphorus, wt%	D-5185	0.07	0.07	0.07
Total Base Number (TBN)	D-2896	1.0	1.0	1.0
Sulfated Ash, wt%	D-4929	<0.10	<0.10	<0.10

**Minor variations in physical test results may occur through normal manufacturing**

**Always consult original equipment manufacturer's lubricant recommendation for proper fluid application.**

