



ZXP 4T Motorcycle Oil

DESCRIPTION

ZXP 4T Motorcycle Oils are formulated using advanced conventional base stocks and a robust additive package to create an ultra-premium conventional engine oil at a value price point. The engine oil can be used in most street bikes, off-road bikes and ATV/UTV applications.

ZXP 4T Motorcycle Oils provide outstanding wear and deposit control during cold engine start-up through maximum operating temperatures. Through its robust additive system, it delivers superior engine protection in all climates and driving conditions.

PERFORMANCE BENEFITS

- Maximize engine power and smooth clutch shifting
- Outstanding anti-wear protection
- Enhanced oxidation and deposit control
- Wet clutch compatible
- Minimal clutch slippage

PRODUCT APPLICATION

ZXP 4T Motorcycle Oil is recommended for:
 JASO MA/MA2
 API SL

Typical Physical Properties						
Property	Method	10W-30	10W-40	15W-40	20W-50	25W-60
SAE Grade		10W-30	10W-40	15W-40	20W-50	25W-60
Viscosity, cSt @40°C	D-445	62.0	96.0	116.0	130.0	232.0
Viscosity, cSt @100°C	D-445	10.7	14.9	15.5	17.4	24.0
Viscosity Index	D-2270	135	145	140	125	125
Specific Gravity, @60°F	D-1250	0.865	0.869	0.878	0.880	0.882
Flash Point, COC, °C(°F)	D-92	220 (428)	232 (450)	236 (457)	235 (455)	236 (457)
Pour Point, °C(°F)	D-97	-44 (-47)	-32 (-26)	-33 (-27)	-30 (-22)	-27 (-17)
Total Base Number (TBN)	D-2896	10.0	10.0	10.0	10.0	10.0
Sulfated Ash, wt. %	D-4929	1.20	1.20	1.20	1.20	1.20

Minor variations in physical test results may occur through normal manufacturing

Always consult original equipment manufacturer's lubricant recommendation for proper fluid application.

