



## ZXP All Season Hydraulic Oil

### DESCRIPTION

ZXP All Season AW Oils are high performing hydraulic fluids formulated with highly refined base stocks and an advanced additive system to deliver optimum equipment protection. All Season AW Oils are formulated with anti-wear, anti-oxidation, anti-foam, and anti-rust additive technology to maximize protection and operation life of equipment.

ZXP All Season Hydraulic AW Oil's high viscosity index delivers peak fluid performance over a wide-range of operating temperatures and conditions and is designed for non-critical hydraulic systems and other general purpose lubrication applications.

### PERFORMANCE BENEFITS

- Protects older hydraulic equipment
- Robust anti wear additives protect critical system components
- Trusted performance over a wide range of operating temperatures and conditions
- Ultimate resistance to rust and oxidation

### PRODUCT APPLICATION

Recommended for use in a variety of farm, off highway construction, logging and industrial equipment. ZXP All Season Hydraulic Oils are suitable for use in aging equipment requiring frequent top off.

Recommended for use in ambient temperatures between 0 deg F and 122 deg F (-16 deg C to 50 deg C)

Typical Physical Properties				
Property	Method			
<b>ISO Grade</b>		<b>32</b>	<b>46</b>	<b>68</b>
Viscosity, cSt @40°C	D-445	32	46	68
Viscosity, cSt @100°C	D-445	6.0	7.5	9.5
Viscosity Index	D-2270	120	120	120
Specific Gravity, @60°F	D-1250	0.8641	0.8667	0.8691
Flash Point, COC, °C(°F)	D-92	176 (350)	176 (350)	176 (350)
Pour Point, (°F)	D-97	-25	-25	-25
Color	D-1500	4.5	4.5	4.5

**Variations in physical test results may occur through normal manufacturing**

Always consult original equipment manufacturer's lubricant recommendation for proper fluid application.

