



ZXP Bar & Chain Oil

DESCRIPTION

ZXP Bar & Chain Oil is specially formulated to provide optimum lubrication of high-speed saw bars and chains over a wide-range of seasonal weather conditions. ZXP Bar & Chain Oil also functions as a solid film agent, delivering boundary lubrication to critical components that operate in dry conditions.

ZXP Bar & Chain Oil is formulated with special rust inhibitors that protect bars and chains when not in operation and anti-wear (AW) and extreme pressure (EP) additives to absorb shock, reduce metal friction and extend the life of bars, chains and sprockets.

PERFORMANCE BENEFITS

- Robust extreme pressure and anti-wear additives protect bars, chains and sprockets
- Anti-sling tackifier additive keeps oil on the chain at high cutting speeds
- Rapid oil penetration provides critical lubrication at saw start-up
- Special rust inhibitors help prevent equipment rust while not in operation or in storage
- Advanced lubricating properties reduce friction and heat build-up on cutting chain and guide bar

PRODUCT APPLICATION

ZXP Bar & Chain Oil is recommended for industrial, commercial and residential chains and saws found in:

- Saw mills
- Forest products industry
- High-speed cutting applications
- Severe operating conditions

Typical Physical Properties		
Property	Method	
Viscosity, cSt @40°C	D-445	108.0
Viscosity, cSt @100°C	D-445	11.5
Specific Gravity, @60°F	D-1250	0.880
Flash Point, COC, °C(°F)	D-92	230 (446)
Pour Point, °C(°F)	D-97	-21 (-6)
Color	D-1500	3.5
Anti-Sling Tackifier		Yes

Minor variations in physical test results may occur through normal manufacturing

Always consult original equipment manufacturer's lubricant recommendation for proper fluid application.

