



## ZXP SAE Motor Oil

### Automotive Formula

#### DESCRIPTION

**ZXP SAE Motor Oil** is formulated with a proprietary blend of conventional base oils and a state-of-the-art additive system to deliver trusted engine protection and peak vehicle performance.

ZXP SAE Motor Oil provides added resistance to sludge formation and varnish deposits during stop-and-go driving and maintains outstanding wear protection under severe driving conditions.

ZXP SAE Motor Oil is available in SAE grades 5W-20, 5W-30 and 10W-30 and exceeds new car warranty requirements as defined by ILSAC standards GF-6A and API classification Resource Conserving SP.

#### PERFORMANCE BENEFITS

- Excellent wear protection for critical engine components
- Delivers excellent low-temperature engine protection and performance
- Maintains maximum engine protection under severe operating conditions
- Protects vehicle emission systems
- Delivers optimum fuel economy

#### PRODUCT APPLICATION

Recommended for turbo-charged or naturally aspirated gasoline-powered and flex-fuel passenger cars, hybrid vehicles, light-trucks and sport utility vehicles and fleets requiring:

ILSAC GF-6A & API Service Category Resource Conserving SP

Chrysler; MS-6395 (Revision S)

Ford; WSS-M2C945-A (5W-20) & WSS-M2C946A (5W-30)

General Motors; GM6094M (Obsolete)

Typical Physical Properties				
Property	Method			
<b>SAE Grade</b>		<b>5W-20</b>	<b>5W-30</b>	<b>10W-30</b>
Viscosity, cSt @40°C	D-445	49.7	63.2	69.5
Viscosity, cSt @100°C	D-445	8.60	10.60	10.60
Viscosity Index	D-2270	150	155	140
Specific Gravity @60°F	D-1250	0.861	0.860	0.866
Flash Point, COC, °C(°F)	D-92	218 (424)	224 (435)	234 (453)
Pour Point, °C(°F)	D-97	-39 (-38)	-39 (-38)	-36 (-33)
CCS, cP, maximum @-30°C	D-5293	6100	6100	5500 (@-25°C)
NOACK Volatility @700°F, % loss	D-5800	<15	<15	<12
Total Base Number (TBN)	D-2896	8.0	8.0	8.0
Sulfated Ash, wt %	D-4929	0.80	0.80	0.80

**Minor variations in physical test results may occur through normal manufacturing**

Always consult original equipment manufacturer's lubricant recommendation for proper fluid application.

