Product Data Sheet

Full Synthetic European Motor Oil

DESCRIPTION

Maverick Full Synthetic Euro Motor Oil is formulated with select synthetic base oils and a state-of-the-art additive system to deliver trusted engine protections and peak vehicle performance.

Maverick Full Synthetic Euro Motor Oil provides added resistance to sludge formation and varnish deposits during stop-and-go driving and maintains outstanding wear protection under severe driving conditions.

PERFORMANCE BENEFITS

- Enhanced emission control system compatibility
- Excellent engine wear protection
- Improved high temperature deposit control for pistons/turbochargers
- Protection against low-speed pre-ignition events
- Stringent resistance to sludge build-up
- Superb oxidation control and limited use oil thickening

PRODUCT APPLICATION

Maverick Full Synthetic Euro Motor Oil is suitable for use where the following specifications and applications are indicated:

ACEA Performance C5	VW Standard 508.00/509.00	Volvo VCC RBS0-2AE
Porsche C20	MB 229.71	STJLR.03.5006
API Service Category SP	BMW LL-17 FE+	STJLR.51.5122

Typical Physical Properties		
Property	**Method**	**0W-20**
Viscosity, cSt @40°C	D-445	38.8
Viscosity, cSt @100°C	D-445	7.5
Viscosity Index	D-2270	165
Specific Gravity, @60°F	D-4052	0.84
Pour Point, °C (°F)	D-5949	-40 (-40)
Total Base Number, mg KOH/g	D-2896	6.8
Sulfated Ash, wt.%	D-4929	0.77
Minor variations in physical test results may occur through normal manufacturing		

Always consult original equipment manufacturer's lubricant recommendation for proper fluid application.

Updated on 6/19/26