Product Data Sheet

Street Power Full Synthetic Motor Oil

DESCRIPTION

Maverick Street Power Full Synthetic Motor Oil is formulated with select synthetic base oils and a state-of-the-art additive system to deliver trusted engine protection and peak vehicle performance. **Maverick Street Power Full Synthetic Motor Oil** provides added resistance to sludge formation and varnish deposits during stop-and-go driving and maintains outstanding wear protection under severe driving conditions.

Maverick Street Power Full Synthetic Motor Oil exceeds new car warranty requirements as defined by ILSAC standard GF-7A and API classification Resource Conserving SQ.

PERFORMANCE BENEFITS

- Provides excellent wear protection for critical engine components
- Delivers excellent low-temperature engine protection and performance
- Maintains maximum engine protection under severe operating conditions
- Provides exceptional thermal and oxidation stability, reducing oil consumption
- Protects vehicle emission systems
- Delivers optimum fuel economy

PRODUCT APPLICATION

Maverick Street Power Full Synthetic Motor Oil is recommended for turbo-charged or naturally aspirated gasoline-powered and flex-fuel passenger cars, hybrid vehicles, light trucks, and sport utility vehicles and fleets where the following are indicated:

ILSAC GF-7A & API Service Category Resource Conserving SQ
Chrysler MS-6395 (Revision S)
Ford, General Motors

Typical Physical Properties					
Property	**Method**	**0W-20**	**5W-20**	**5W-30**	**10W-30**
Viscosity @ 40°C, cSt	D-445	44.8	44.5	63.9	65.0
Viscosity @ 100°C, cSt	D-445	8.40	8.26	11.0	10.5
Viscosity Index	D-2270	169	163	167	150
Specific Gravity @ 60°F, g/mL	D-4052	0.85	0.84	0.85	0.85
Flash Point, °C (°F)	D-92	230 (446)	235 (455)	235 (455)	235 (455)
Pour Point, °C (°F)	D-5949	-42 (-44)	-36 (-33)	-36 (-33)	-36 (-33)
Cold Crank Viscosity, cP	D-5293	5600 (@ -30°C)	3600 (@ -30°C)	4900 (@ -30°C)	3500 (@ -25°C)
Noack Volatility @ 700°F, % loss	D-5800	< 12	< 12	< 13	< 13
Total Base Number, mg KOH/g	D-2896	7.5	7.5	7.5	7.5
Sulfated Ash, wt.%	D-4929	0.8	0.8	0.8	0.8
Minor variations in physical test results may occur through normal manufacturing					

Always consult original equipment manufacturer's lubricant recommendation for proper fluid application.
Updated on 7/19/26