Product Data Sheet

Fleet Power Red Hi-Temp Grease EP 2

DESCRIPTION

Maverick Fleet Power Red Hi-Temp Grease is a premium, high-temperature, lithium complex grease designed for a wide range of demanding applications. It is formulated with extreme pressure (EP) additives, anti-wear additives, and long-lasting corrosion and oxidation inhibitors. **Maverick Fleet Power Red Hi-Temp Grease** delivers maximum protection and trouble-free operation in lubrication applications found in automotive, heavy-duty trucking, construction, agriculture, mining, and industrial service.

PERFORMANCE BENEFITS

- Special EP and anti-wear properties protect critical components under extreme load
- Outstanding resistance to corrosion extends equipment life
- Excellent shock load protection for heavy-duty equipment
- Optimum high-temperature performance delivers resistance to grease softening
- Excellent EP wear performance delivers maximum protection in severe applications
- Maintains grease consistency and lubricating film strength under heavy load
- Inherent tackiness properties prevent bearing drop out and resists water washout
- NLGI certification GC-LB application for wheel bearing and heavy-duty chassis lubrication

PRODUCT APPLICATION

Maverick Fleet Power Red Hi-Temp Grease is recommended for the most demanding lubricating grease applications, including:

- Disk and drum brake wheel bearings
- Industrial ball and roller bearings
- Heavy-duty chassis and ball & universal joint lubrication
- Boat trailer & 5th wheel lubrication
- Conveyor bearings & equipment hinge pins

Typical Properties		
Property	**Method**	
NLGI Consistency		2
NLGI Certification		GC-LB
Thickener Soap Type		Lithium Complex
Texture		Smooth-Tacky
Color	Visual	Red
Dropping Point, °F (°C), Minimum	D-2265	428 (220)
Water Washout @ 175°F, % loss, Maximum	D-1264	15
Wear Protection, Scar Diameter, mm, Maximum	D-2266	0.6
Worked Penetration, 60 strokes	D-217	280
Oil Separation, Mass %, Maximum	D-1742	6
Rust Prevention	D-1743	Pass
Four-Ball Weld Point, kfg, Minimum	D-2596	200
Four-Ball Load Wear Index, kfg	D-2596	30
Wheel Bearing Life, Hours, Minimum	D-3527	80
Leakage Tendencies, Weight loss, grams, Maximum	D-4290	10
Fretting Protection, mass loss, mg, Maximum	D-4170	10
Low-Temperature Performance, torque @ -40°C, Nm, Maximum	D-4693	15.5
Minor variations in physical test results may occur through normal manufacturing		

Always consult original equipment manufacturer's lubricant recommendation for proper fluid application.

Updated on 7/8/26